

AERO TAPE FREE CUT

Indoor · Static White

Features

- Small increment cuttable every 0.33in. (8.3mm) spacing of diode
- IP20 rated, ideal for indoor non-condensing uses
- 5 years warranty

Applications

Under cabinets, coves, shelves, bedrooms, offices, hallways, etc.



Dimensions



Order Code (For LED tape)

Series	Environment	Voltage	CCT	Power	Left Feed Entry			
AEROFC	D2-Dry (IP20)	24V-DC24V	18K-1800K	3.7-3.66W/ft	F	Front	OW	Open wire 3.28ft (1m), 20 AWG
			22K-2200K	4.3-4.27W/ft	C	Closed	MC	Male connector with 0.66ft (20cm) cable, 20 AWG
			24K-2400K	5.8-5.79W/ft			FC	Female connector with 0.66ft (20cm) cable, 20 AWG
			27K-2700K				NA	Only for Closed Feed Entry
			30K-3000K					
			35K-3500K					
			40K-4000K					

Assembly Builder

Assembly Builder

Right Feed Entry				Length
F	Front	OW	Open wire 3.28ft (1m), 20 AWG	Increment 0.33in. (8.3mm)
C	Closed	MC	Male connector with 0.66ft (20cm) cable, 20 AWG	
		FC	Female connector with 0.66ft (20cm) cable, 20 AWG	
		NA	Only for Closed Feed Entry	

*For customizations, please inquire.

Channel Order Code

Product Code	Colors	Lens	Lengths
Please select on the Extrusion Compatibility page	S = Silver anodized	OP - Opal	3.28ft (1m)
	W = White lacquered	FR - Frosted	6.56ft (2m)
	B = Black anodized	CL - Clear	

*For custom RAL colors, please inquire.

*Extrusions are sold separately. Refer to corresponding spec sheets for ordering info on extrusions and their accessories (endcaps, mounting brackets, etc.)

CCT	3.66W/ft	4.27W/ft	5.79W/ft
1800K	288	335	453
2200K	299	347	470
2400K	310	360	487
2700K	327	380	514
3000K	338	392	531
3500K	341	396	536
4000K	352	409	553
Max. Run for Class 2*	21.9ft (6.7m)	18.7ft (5.7m)	13.8ft (4.2m)
Max. Run Supported Length	26.2ft (8m)	19.7ft (6m)	19.7ft (6m)

*Typically installations in USA and Canada comply with Class 2 requirements.

Technical Details

Width	0.39in. (10mm)
LED Quantity	36 LEDs/ft (120 LEDs/m)
Beam Angle	120°
Efficacy	95.8lm/W @4000K 4.27W
CRI	Ra ≥ 90
LED MacAdam	3 steps
Average Life (L70)	> 54,000 hours
Max. Length Per Reel	164ft (50m)
Storage Temperature	-4-113°F (-20°C- 60°C)
Ambient Temperature	-13-140°F (-20°C- 45°C)

Feed Entry Options

F: Front



C: Closed



Connector Wire Options

OW: Open wire, Dry only

Standard 3.28ft (1m), 20 AWG
(wire length made to order)

MC: Male connector, Dry & Damp

Standard 0.66ft (20cm), 20 AWG

FC: Female connector, Dry & Damp

Standard 0.66ft (20cm), 20 AWG

AERO TAPE FREE CUT

Indoor · Static White

Channel Compatibility

* Non-standard option, please contact us for customization support.

Lens Type & Light Transmission

CL Clear FR Frosted OP Opal

Surface				
BE1202 CL 63%FR 58%OP 47%		BE1415 CL 54%FR 49%OP 40%		
Mud-In				
BE5615 CL 60%FR 55%OP 45%		BE7615 CL 72%FR 66%OP 54%		
Recessed				
BE1201 CL 62%FR 56%OP 46%		BE1207 CL 62%FR 57%OP 46%	BE2015 CL 55%FR 50%OP 41%	BE5035 CL 55%FR 50%OP 41%
BE6575 CL 65%FR 59%OP 48%				

AERO TAPE FREE CUT

Indoor · Static White

Suspended

BE3535	BE5075
CL 56% FR 51% OP 41%	CL 64% FR 58% OP 48%
(25.5mm) height, 1.38"/>(35mm) width, 1.02"/>(25.9mm) internal width, and 1.38"/>(35mm) base width."/>	(75mm) height, 1.24"/>(31.6mm) internal width, 1.61"/>(41mm) base width, 1.97"/>(50mm) total width, and 1.04"/>(26.4mm) top flange width."/>

Specialty

BE5315 Borderless Outside Corner	BE4615 Borderless Inside Corner	BE8833 Cove Recessed / Double-Layer Borderless
CL 58% FR 53% OP 43%	CL 59% FR 54% OP 44%	CL 58% FR 53% OP 43%
(15.5mm) top flange, 0.49"/>(12.5mm) internal width, 0.59"/>(15mm) height, 0.39"/>(10mm) base, 2.12"/>(53.8mm) total width, and 90° angle."/>	(46.7mm) top flange, 0.61"/>(15.5mm) internal width, 0.49"/>(12.5mm) base, 1.22"/>(30.9mm) total width, 90° angle, and 0.43"/>(11mm) side flange."/>	(87.6mm) top flange, 1.38"/>(35mm) internal width, 0.55"/>(14mm) height, 0.96"/>(24.5mm) base, 0.47"/>(12mm) side flange, 1.30"/>(33mm) total width, and 1.19"/>(30.3mm) internal width."/>

Connectors & Additional Accessories (Optional, purchase for extra)

**N6012-STCN-2P-10**

Strip to cable connector without wire, for 0.39" (10mm) tape, 2 pin, IP20

**N6012-STC-2P-10**

Strip to cable connector with 5.91" (15cm) wire, for 0.39" (10mm) tape, 2 pin, IP20

**N6012-STSJ-2P-10**

Strip to strip jumper connector with 5.91" (15cm) wire, for 0.39" (10mm) tape, 2 pin, IP20

**N6012-STDCB-2P-10**

Strip to cable with black male & female connector, for 0.39" (10mm) tape, 2 pin, IP20

**N6012-STDCW-2P-10**

Strip to cable with white male & female connector, for 0.39" (10mm) tape, 2 pin, IP20

**N6012-ST5-2P-10**

Strip to strip connector, for 0.39" (10mm) tape, 2 pin, IP20

**C6012-LC-2P-10**

L-shaped corner connector, for 0.39" (10mm) tape, 2 pin, IP20

**C6012-RC-2P-10**

R-shaped corner connector, for 0.39" (10mm) tape, 2 pin, IP20

**MCB-DC-44**

Male DC connector with 0.66" (20cm) cable, IP44, Dry & damp, 20 AWG

**FCB-DC-44**

Female DC connector with 0.66" (20cm) cable, IP44, Dry & damp, 20 AWG

AERO TAPE FREE CUT

Indoor · Static White

Drivers

Non-dimmable							
Code	Max Load	Input	Output	Class 2	With Junction Box	Environment	Size (L x W x H)
KV-24030-ASW	30W	100-277VAC	24V	Yes	No	Dry/Damp	6.1 x 2.1 x 0.8in. (15.5 x 5.4 x 2cm)
KV-24060-ASW	60W						7 x 2.4 x 0.9in. (17.8 x 6.1 x 2.4cm)
KV-24096-ASW	96W					Dry/Damp/Wet	9.1 x 2.8 x 1.7in. (23 x 7 x 4.3cm)

Phase cut/Triac-dimmable							
Code	Max Load	Input	Output	Class 2	With Junction Box	Environment	Size (L x W x H)
KVF-24030-TDW	30W	100-277VAC	24V	Yes	No	Dry/Damp	6.1 x 2.1 x 0.8in. (15.5 x 5.4 x 2cm)
KVF-24060-TDW	60W						7 x 2.4 x 0.9in. (17.8 x 6.1 x 2.4cm)
KVF-24096-TDW	96W					Dry/Damp/Wet	9.1 x 2.8 x 1.7in. (23 x 7 x 4.3cm)
KVF-24030-TDWJ	30W				Yes	Dry/Damp	6.5 x 3.6 x 1in. (16.5 x 9.2 x 2.6cm)
KVF-24060-TDWJ	60W						7.4 x 3.6 x 1in. (18.8 x 9.2 x 2.6cm)
KVF-24096-TDWJ	96W						8.7 x 3.7 x 1.6in. (22 x 9.3 x 4.1cm)
KVF-24192-TDWJ	192W (96Wx2)						10.9 x 4.3 x 1.8in. (27.8 x 11 x 4.5cm)
KVF-24288-TDWJ	288W (96Wx3)						11.9 x 4.3 x 1.8in. (30.1 x 11 x 4.5cm)
KVF-24384-TDWJ	384W (96Wx4)						12.7 x 5.5 x 1.9in. (32.3 x 14 x 4.8cm)

4 in 1-dimmable (0-10V/1-10V/Potentiometer/10V PWM)							
Code	Max Load	Input	Output	Class 2	With Junction Box	Environment	Size (L x W x H)
KVD-24030-DIM	30W	100-277VAC	24V	Yes	No	Dry/Damp	6.1 x 2.1 x 0.8in. (15.5 x 5.4 x 2cm)
KVD-24060-DIM	60W						7 x 2.4 x 0.9in. (17.8 x 6.1 x 2.4cm)
KVD-24096-DIM	96W					Dry/Damp/Wet	9.1 x 2.8 x 1.7in. (23 x 7 x 4.3cm)
KVD-24030-DIMJ	30W				Yes	Dry/Damp	6.5 x 3.6 x 1in. (16.5 x 9.2 x 2.6cm)
KVD-24060-DIMJ	60W						7.4 x 3.6 x 1in. (18.8 x 9.2 x 2.6cm)
KVD-24096-DIMJ	96W						8.7 x 3.7 x 1.6in. (22 x 9.3 x 4.1cm)
KVD-24192-DIMJ	192W (96Wx2)						10.9 x 4.3 x 1.8in. (27.8 x 11 x 4.5cm)
KVD-24288-DIMJ	288W (96Wx3)						11.9 x 4.3 x 1.8in. (30.1 x 11 x 4.5cm)
KVD-24384-DIMJ	384W (96Wx4)						12.7 x 5.5 x 1.9in. (32.3 x 14 x 4.8cm)


5 in 1-dimmable (Triac/0-10V/1-10V/Potentiometer/10V PWM)							
Code	Max Load	Input	Output	Class 2	With Junction Box	Environment	Size (L x W x H)
KVG-24030-DW	30W	100-277VAC	24V	Yes	No	Dry/Damp	6.1 x 2.1 x 0.8in. (15.5 x 5.4 x 2cm)
KVG-24060-DW	60W						7 x 2.4 x 0.9in. (17.8 x 6.1 x 2.4cm)
KVG-24096-DW	96W					Dry/Damp/Wet	9.1 x 2.8 x 1.7in. (23 x 7 x 4.3cm)
KVG-24030-DWJ	30W				Yes	Dry/Damp	6.5 x 3.7 x 1.6in. (16.5 x 9.5 x 4cm)
KVG-24060-DWJ	60W						7.4 x 3.7 x 1.6in. (18.8 x 9.5 x 4cm)
KVG-24096-DWJ	96W						8.7 x 3.7 x 1.6in. (22 x 9.5 x 4cm)
KVG-C24192-DWJ	192W (96Wx2)						10.9 x 4.3 x 1.8in. (27.8 x 11 x 4.5cm)
KVG-C24288-DWJ	288W (96Wx3)						11.9 x 4.3 x 1.8in. (30.1 x 11 x 4.5cm)
KVG-C24384-DWJ	384W (96Wx4)						12.8 x 5.5 x 1.9in. (32.5 x 14 x 4.8cm)

AERO TAPE FREE CUT


Indoor · Static White

Wiring Diagram


Non-dimmable




Phase cut/Triac-dimmable



4 in 1-dimmable (0-10V/1-10V/Potentiometer/10V PWM)



5 in 1-dimmable (Triac/0-10V/1-10V/Potentiometer/10V PWM)



AERO TAPE FREE CUT Indoor · Static White

24V Voltage Drop & Maximum Wire Length Chart

Based on 24V voltage with a 3% voltage drop allowance. Indicates the maximum wire length from the power supply to the start of the run.

Total Load	10 AWG	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG	24 AWG
5W / 0.2A	1730 ft(527.3 m)	1090 ft(332.2 m)	680 ft (207.3 m)	430 ft (131.1 m)	270 ft (82.3 m)	170 ft (51.8 m)	107 ft (32.6 m)	68 ft (20.7 m)
10W / 0.4A	784 ft (239.0 m)	539 ft (164.3 m)	345 ft (105.2 m)	215 ft (65.5 m)	134 ft (40.8 m)	85 ft (25.9 m)	52 ft (15.8 m)	34 ft (10.4 m)
15W / 0.6A	576 ft (175.6 m)	363 ft (110.6 m)	228 ft (69.5 m)	144 ft (43.9 m)	91 ft (27.7 m)	57 ft (17.4 m)	36 ft (11.0 m)	23 ft (7.0 m)
20W / 0.8A	397 ft (121.0 m)	272 ft (82.9 m)	174 ft (53.0 m)	109 ft (33.2 m)	68 ft (20.7 m)	43 ft (13.1 m)	27 ft (8.2 m)	17 ft (5.2 m)
25W / 1.0A	346 ft (105.5 m)	218 ft (66.4 m)	137 ft (41.8 m)	86 ft (26.2 m)	55 ft (16.8 m)	34 ft (10.4 m)	22 ft (6.7 m)	14 ft (4.3 m)
30W / 1.2A	263 ft (80.2 m)	181 ft (55.2 m)	115 ft (35.1 m)	72 ft (21.9 m)	45 ft (13.7 m)	27 ft (8.2 m)	17 ft (5.2 m)	12 ft (3.7 m)
35W / 1.5A	247 ft (75.3 m)	156 ft (47.5 m)	98 ft (29.9 m)	62 ft (18.9 m)	39 ft (11.9 m)	25 ft (7.6 m)	16 ft (4.9 m)	10 ft (3.0 m)
40W / 1.7A	197 ft (60.0 m)	135 ft (41.1 m)	86 ft (26.2 m)	54 ft (16.5 m)	33 ft (10.1 m)	21 ft (6.4 m)	13 ft (4.0 m)	9 ft (2.7 m)
45W / 1.9A	192 ft (58.5 m)	121 ft (36.9 m)	76 ft (23.2 m)	48 ft (14.6 m)	31 ft (9.4 m)	19 ft (5.8 m)	12 ft (3.7 m)	8 ft (2.4 m)
50W / 2.1A	158 ft (48.2 m)	108 ft (32.9 m)	69 ft (21.0 m)	43 ft (13.1 m)	27 ft (8.2 m)	17 ft (5.2 m)	10.5 ft (3.2 m)	7 ft (2.1 m)
60W / 2.5A	131 ft (39.9 m)	90 ft (27.4 m)	57 ft (17.4 m)	36 ft (11.0 m)	22 ft (6.7 m)	14 ft (4.3 m)	9 ft (2.7 m)	6 ft (1.8 m)
70W / 2.9A	112 ft (34.1 m)	77 ft (23.5 m)	49 ft (14.9 m)	31 ft (9.4 m)	19 ft (5.8 m)	12 ft (3.7 m)	7.5 ft (2.3 m)	5 ft (1.5 m)
80W / 3.3A	98 ft (29.9 m)	68 ft (20.7 m)	43 ft (13.1 m)	27 ft (8.2 m)	17 ft (5.2 m)	11 ft (3.4 m)	6.8 ft (2.1 m)	5 ft (1.5 m)
90W / 3.8A	97 ft (29.6 m)	61 ft (18.6 m)	39 ft (11.9 m)	24 ft (7.3 m)	15 ft (4.6 m)	9 ft (2.7 m)	6 ft (1.8 m)	4 ft (1.2 m)
100W / 4.2A	82 ft (25.0 m)	56 ft (17.1 m)	36 ft (11.0 m)	22 ft (6.7 m)	14 ft (4.3 m)	8 ft (2.4 m)	5.3 ft (1.6 m)	4 ft (1.2 m)