

# AERO TAPE MIRROR Indoor · Tunable White

## Features

- Ra 95+
- Field cuttable & joinable
- Low voltage DC24V
- 500 lumen outputs
- IP20 rated, ideal for indoor uses
- 5 years warranty




Date \_\_\_\_\_ Fixture type \_\_\_\_\_

Project name \_\_\_\_\_ Project phase \_\_\_\_\_



## Dimension



## Order Code

Series	Environment	Voltage	Temp./Color	Power
AEROM	D2 Dry (IP20)	24 DC24V	2765 2700K+6500K	564 5.64W/ft ~500 lm/ft

## Assembly Builder

Left Feed Entry				Right Feed Entry				Illuminated Length¹		
F	Front	OW	Open wire 3.28'	F	Front	OW	Open wire 3.28'	Max.	32.8'	~5.64W
C	Closed	MC	Male connector with 0.98' cable	C	Closed	MC	Male connector with 0.98' cable	Increment	1.97'	
		FC	Female connector with 0.98' cable			FC	Female connector with 0.98' cable			
		NA	Only for Closed Feed Entry			NA	Only for Closed Feed Entry			

Temp./Color	5.64W/ft
2700K	270
6500K	209
2700K+6500K	566
Max. Run for Class 2 Low Voltage (ft)	13.6
Max. Run Length (ft)	32.8
Storage Temperature	32-140°F
Ambient Temperature	-4-104°F

## Technical Details


Width	0.39" (10mm)
PCB Width	0.39" (10mm)
LED Quantity	36 LEDs/ft (120 LEDs/M)
Beam Angle	120°
Efficacy	100.4lm/W @2700K+6500K 5.64W
CRI	Ra≥95
LED MacAdam	2 steps
Life (L70)	> 102,000 hours
Max. Length Per Reel	164' (50M)

## Feed Entry Options

F: Front



C: Closed



## Connector Wire Options



**OW:** Open wire, **Dry only**  
Standard 3.28' (1m), 20 AWG  
(wire length customizable)




**MC:** Male connector, **Wet**  
Standard 0.98' (30cm), 20 AWG



**FC:** Female connector, **Wet**  
Standard 0.98' (30cm), 20 AWG


# AERO TAPE MIRROR Indoor · Tunable White

## Channel Compatibility


: No pixelation

### Universal


BEI215




BEI815




BEI415




BE2015




BEI202



BEI201




BEI207




### Architectural


BE5615




BE7615




BE5315




BE4615




BE5035




BE3535



BE5075




BE8833




### Main lighting


BE6575



BE9358




BE60




### Special lighting

BE6728




BE2009




## AERO TAPE MIRROR Indoor · Tunable White

: Slight pixelation

### Universal



### Special lighting




### Drivers

#### Dimmable

Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L *W *H)
LM-I00-24-U2A2	100W	100-277VAC	24V	Yes	No	Dry	13.86" *1.69" *1.18"

### Wiring Diagram

#### Dimmable



AERO TAPE MIRROR Indoor · Tunable White

Connectors (Optional, purchase for extra)



**N6012-STCN-3P-10**  
Strip to cable connector without wire, for 0.39" (10mm) tape, 3 pin



**N6012-STC-3P-10**  
Strip to cable connector with 5.91" (15cm) wire, for 0.39" (10mm) tape, 3 pin



**N6012-STSJ-3P-10**  
Strip to strip jumper connector with 5.91" (15cm) wire, for 0.39" (10mm) tape, 3 pin



**N6012-STMKB-3P-10**  
Strip to cable with black male & female connector, for 0.39" (10mm) tape, 3 pin



**N6012-STMKW-3P-10**  
Strip to cable with white male & female connector, for 0.39" (10mm) tape, 3 pin



**N6012-STS-3P-10**  
Strip to strip connector, for 0.39" (10mm) tape, 3 pin



**C6012-LC-3P-10**  
L-shaped corner connector, for 0.39" (10mm) tape, 3 pin



**C6012-RC-3P-10**  
R-shaped corner connector, for 0.39" (10mm) tape, 3 pin

Additional Accessories (Optional, purchase for extra)



**MCW-3P-67**  
Male connector with 0.98' (30cm) white cable, 3 pin, IP67, Wet, 20 AWG



**FCW-3P-67**  
Female connector with 0.98' (30cm) white cable, 3 pin, IP67, Wet, 20 AWG



**VHB**  
VHB 3M adhesive back tape, stronger stickiness