

BELA TAPE RGB Indoor · RGB

Features


- Max run length up to 16.4ft (5m) from single power feed
- Field cuttable
- Low voltage DC24V
- 200 lumen outputs
- IP20 rated, ideal for indoor uses
- 5 years warranty



Date	Fixture type
Project name	Project phase



Dimension



Order Code

Series	Environment	Voltage	Temp./Color	Power
BELA	D2 Dry (IP20)	24 DC24V	RGB RGB	439 4.39W/ft ~200 lm/ft

Assembly Builder

Left Feed Entry				Right Feed Entry				Illuminated Length ¹		
F Front	OW	Open wire 3.28'		F Front	OW	Open wire 3.28'		Max.	16.4'	~4.39W
C Closed	MC	Male connector with 0.98' cable		C Closed	MC	Male connector with 0.98' cable		Increment	3.94'	
	FC	Female connector with 0.98' cable			FC	Female connector with 0.98' cable				
	NA	Only for Closed Feed Entry			NA	Only for Closed Feed Entry				

1. Production length = Illuminated length + End cap extension length (refer to below page for extension length of each end cap)

Temp./Color	4.39W/ft
R	32
G	128
B	24
RGB	176
Max. Run for Class 2 Low Voltage (ft)	13.1
Max. Run Length (ft)	16.4
Storage Temperature	-13-140°F
Ambient Temperature	-4-113°F

Technical Details

Width	0.39" (10mm)
PCB Width	0.39" (10mm)
LED Quantity	18 LEDs/ft (60 LEDs/M)
Beam Angle	120°
Efficacy	40.1lm/W @RGB 4.39W
LED MacAdam	3 steps
Life (L70)	> 30,000 hours
Max. Length Per Reel	164' (50M)

Feed Entry Options



Connector Wire Options



OW: Open wire, **Dry only**
Standard 3.28' (1m), 20 AWG (wire length customizable)

MC: Male connector, **Wet**
Standard 0.98' (30cm), 20 AWG

FC: Female connector, **Wet**
Standard 0.98' (30cm), 20 AWG


BELA TAPE RGB Indoor · RGB

Channel Compatibility


: No pixelation

Architectural


BE5035




BE3535




BE5075



BE8833




BE5615




Main lighting


BE6575



BE9358




BE60



Special lighting


BE2009




: Slight pixelation

Universal


BE1215




BE1815




BE1415




BE2015




BE1202




BE1201



BE1207




BE1203




Architectural

BE7615




BE5315



BELA TAPE RGB Indoor · RGB

Special lighting

BE6728



Drivers

Non-dimmable

Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L *W *H)
KV-24030-ASW	30W	100-277VAC	24V	No	Yes	Dry/Damp	6.10" *2.12" *0.78"
KV-24060-ASW	60W	100-277VAC	24V	No	Yes	Dry/Damp	7.00" *2.40" *0.94"
KV-24096-ASW	96W	100-277VAC	24V	No	Yes	Dry/Damp/Wet	9.05" *2.75" *1.69"
KV-24150-ASW	150W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.07" *3.07" *1.85"
KV-24200-ASW	200W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.07" *3.07" *1.85"
KV-24300-ASW	300W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.86" *3.07" *1.85"

DMX512-dimmable

Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L *W *H)
KVX-24096-3C-A	96W	100-277VAC	24V	Yes	Yes	Dry/Damp/Wet	9.05" *3.07" *0.98"
KVX-24150-3C-A	150W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.90" *3.07" *0.98"
KVX-24200-3C-A	200W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.90" *3.07" *0.98"
KVX-24300-3C-A	300W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	11.85" *3.07" *0.98"

DMX Decoders


Code	Description
LT-903	3 channels output, up to 576W output power
LT-912	12 channels output, up to 1152W output power
LT-924	24 channels output, up to 1728W output power

Controllers


Code	Description
DINA-DR micro	DMX 60 channels, DMX Stand Alone controller with 10 scenes, USB connectivity for programming
SLESA-U9	DMX 256 channels, USB connection, standalone mode with 1 area and 20 scenes
STICK-GA2	DMX 512 channels, ready to use (pre-loaded with 8 scenes and 170 RGB fixtures)
STICK-CW4	DMX 1024 channels, up to 36 scenes stored and directly recalled via 6 touch sensitive buttons

Wiring Diagram

DMX Control System



DMX Driver System



Additional Accessories (Optional, purchase for extra)



MCW-4P-67

Male connector with 0.98' (30cm) white cable, 4 pin, IP67, Wet, 20 AWG

FCW-4P-67

Female connector with 0.98' (30cm) white cable, 4 pin, IP67, Wet, 20 AWG

VHB

VHB 3M adhesive back tape, stronger stickiness