

LINIO NEON 1617 SV SPOT

Horizontal Bending · Static White


Features

- Max run length up to 16.4ft (5m) from single power feed
- Low voltage DC24V
- 400 lumen output
- Flexible asymmetric elliptical optic
- IP67 rated, ideal for indoor and outdoor uses
- 5 years warranty



Date	Fixture type
Project name	Project phase

Dimension



Series	Environment	Voltage	Temp./Color	Power
LN1617SVST	W7	Wet (IP67)	24	DC24V
			22	2200K
			27	2700K
			30	3000K
			35	3500K
			40	4000K
			50	5000K
				549
				5.49W/ft
				-400lm/ft

Assembly Builder

End Cap	Left Feed Entry	Right Feed Entry	Illuminated Length
IJ Injected (IP67)	F Front OW Open wire 3.28'	F Front OW Open wire 3.28'	Max 16.4' -5.49W
IJC Clear injected (IP67)	B Bottom MC Male connector with 0.98' cable	B Bottom MC Male connector with 0.98' cable	Increment 0.13'
SEC Silicone (IP67)	S Side FC Female connector with 0.98' cable	S Side FC Female connector with 0.98' cable	
	C Closed NA Only for Closed Feed Entry	C Closed NA Only for Closed Feed Entry	

Temp./Color	5.49W/ft
2200K	376
2700K	417
3000K	436
3500K	449
4000K	448
5000K	441
Max. Run Length (ft)	16.4
Storage Temperature	-13-140°F
Ambient Temperature	-13-140°F

Technical Details


Efficacy	79.4 lm/W @3000K 5.49W
CRI	Ra > 90
Beam Angle	Asymmetric elliptical optic
Max. Length Per Reel	65.6' (20M)

LINIO NEON 1617 SV SPOT


Horizontal Bending · Static White

Feed Entry / End Cap Options


IJ: Injected end cap – IP67, factory-made only



IJC: Clear injected end cap – IP67, factory-made only



SEC: Silicone end cap – IP67



Connector Wire Options



OW: Open wire, **Dry only**
Standard 1m (3.28'), 18 AWG (wire length customizable)



MC: Male connector, **Wet**
Standard 30cm (0.98'), 18 AWG




FC: Female connector, **Wet**
Standard 30cm (0.98'), 18 AWG

LINIO NEON 1617 SV SPOT


Horizontal Bending · Static White

Mounting Options




LINI617-SC

Name	Straight surface channel
Material	Aluminum
Standard Length	3.28' (IM)




LINI617-BC

Name	Bendable surface channel
Material	Aluminum
Standard Length	3.28' (IM)




LINI617-RC

Name	Straight recessed channel
Material	Aluminum
Standard Length	3.28' (IM)




LINI617-MC

Name	Mud-in channel
Material	Aluminum
Standard Length	3.28' (IM)




LINI617-BMC

Name	Bendable mud-in channel
Material	Aluminum
Standard Length	3.28' (IM)




LINI617-LBC

Name	Light-block channel
Material	Aluminum
Standard Length	3.28' (IM)




LINI617-PC

Name	PC channel
Material	Polycarbonate
Standard Length	3.28' (IM)



LINI617-CL

Name	Mounting clip
Material	Aluminum
Standard Length	0.98' (25MM)




LINI617-LS

Name	L-shaped mounting bracket
Material	Aluminum
Standard Length	0.79' (20MM)

LINIO NEON 1617 SV SPOT

Horizontal Bending · Static White



LN1617-AC

Name	Adjustable mounting clip
Material	Stainless steel
Standard Length	1" (25.5MM)

Drivers

Non-dimmable

Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L *W *H)
KV-24030-ASW	30W	100-277VAC	24V	No	Yes	Dry/Damp	6.10" *2.12" *0.78"
KV-24060-ASW	60W	100-277VAC	24V	No	Yes	Dry/Damp	7.00" *2.40" *0.94"
KV-24096-ASW	96W	100-277VAC	24V	No	Yes	Dry/Damp/Wet	9.05" *2.75" *1.69"
KV-24150-ASW	150W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.07" *3.07" *1.85"
KV-24200-ASW	200W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.07" *3.07" *1.85"
KV-24300-ASW	300W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.86" *3.07" *1.85"

Phase cut/Triac-dimmable

Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L *W *H)
KVF-24030-TDW	30W	100-277VAC	24V	Yes	Yes	Dry/Damp	6.10" *2.12" *0.78"
KVF-24060-TDW	60W	100-277VAC	24V	Yes	Yes	Dry/Damp	7.00" *2.40" *0.94"
KVF-24096-TDW	96W	100-277VAC	24V	Yes	Yes	Dry/Damp/Wet	9.05" *2.75" *1.69"
KVF-24150-TDW	150W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.00" *3.07" *1.85"
KVF-24200-TDW	200W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.00" *3.07" *1.85"
KVF-24300-TDW	300W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.87" *3.07" *1.85"

4 in 1-dimmable (0-10V/1-10V/Potentiometer/10V PWM)


Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L *W *H)
KVD-24030-DIM	30W	100-277VAC	24V	Yes	Yes	Dry/Damp	6.10" *2.12" *0.78"
KVD-24060-DIM	60W	100-277VAC	24V	Yes	Yes	Dry/Damp	7.01" *2.40" *0.94"
KVD-24096-DIM	96W	100-277VAC	24V	Yes	Yes	Dry/Damp/Wet	9.05" *2.75" *1.69"
KVD-24150-DIM	150W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.08" *3.07" *1.85"
KVD-24200-DIM	200W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	13.38" *11.02" *7.28"
KVD-24300-DIM	300W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.87" *3.07" *1.89"

5 in 1-dimmable (Triac/0-10V/1-10V/Potentiometer/10V PWM)


Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L *W *H)
KVG-24030-DW	30W	100-277VAC	24V	Yes	Yes	Dry/Damp	6.10" *2.13" *0.79"
KVG-24060-DW	60W	100-277VAC	24V	Yes	Yes	Dry/Damp	7.01" *2.41" *0.94"
KVG-24096-DW	96W	100-277VAC	24V	Yes	Yes	Dry/Damp/Wet	9.06" *2.76" *1.69"
KVG-24150-DW	150W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.08" *3.07" *1.85"
KVG-24200-DW	200W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.08" *3.07" *1.85"
KVG-24300-DW	300W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.87" *3.07" *1.89"

Wiring Diagram

Non-dimmable




Triac Dimmable



LINIO NEON 1617 SV SPOT

Horizontal Bending · Static White

Connectors (Optional, purchase for extra)



- LNI617-SEC-C**
Silicone closed end cap
- LNI617-SEC-F-2P**
Silicone end cap front entry with 0.98' (30cm) cable, 2 pin
- LNI617-SEC-S-2P**
Silicone end cap side entry with 0.98' (30cm) cable, 2 pin
- LNI617-SEC-B-2P**
Silicone end cap bottom entry with 0.98' (30cm) cable, 2 pin

Additional Accessories (Optional, purchase for extra)



- MCW-2P-67**
Male connector with 0.98' (30cm) white cable, 2 pin, IP67, Wet, 18 AWG
- FCW-2P-67**
Female connector with 0.98' (30cm) white cable, 2 pin, IP67, Wet, 18 AWG
- MCB-2P-67**
Male connector with 0.98' (30cm) black cable, 2 pin, IP67, Wet, 18 AWG
- FCB-2P-67**
Female connector with 0.98' (30cm) black cable, 2 pin, IP67, Wet, 18 AWG