

NOVA TAPE PRO RGB Indoor · RGB

Features

- White COB with clean look, better color consistency
- Field cuttable & joinable
- Low voltage DC24V
- 180 lumen outputs
- IP20 rated, ideal for indoor uses
- 5 years warranty



Date


Fixture type

Project name

Project phase



Dimension



Order Code

Series	Environment	Voltage	Temp./Color	Power
NOVAP	D2 Dry (IP20)	24 DC24V	RGB RGB	457 4.57W/ft ~100 lm/ft

Assembly Builder

Left Feed Entry				Right Feed Entry				Illuminated Length ¹		
F	Front	OW	Open wire 3.28'	F	Front	OW	Open wire 3.28'	Max.	16.4'	~4.57W
C	Closed	MC	Male connector with 0.98' cable	C	Closed	MC	Male connector with 0.98' cable	Increment	1.97'	
		FC	Female connector with 0.98' cable			FC	Female connector with 0.98' cable			
		NA	Only for Closed Feed Entry			NA	Only for Closed Feed Entry			

Temp./Color	4.57W/ft
R	43
G	123
B	25
RGB	180
Max. Run for Class 2 Low Voltage (ft)	16.4
Max. Run Length (ft)	16.4
Storage Temperature	-13~140°F
Ambient Temperature	-4~113°F

Technical Details

Width	0.39" (10mm)
PCB Width	0.39" (10mm)
LED Quantity	256 LEDs/ft (840 LEDs/m)
Beam Angle	120°
Efficacy	39.4lm/W @RGB 4.57W
Life (L70)	> 30,000 hours
Max. Length Per Reel	98.4' (30m)

Feed Entry Options

F: Front



C: Closed



Connector Wire Options



OW: Open wire, **Dry only**
Standard 3.28' (1m), 20 AWG
(wire length customizable)



MC: Male connector, **Wet**
Standard 0.98' (30cm), 20 AWG




FC: Female connector, **Wet**
Standard 0.98' (30cm), 20 AWG

NOVA TAPE PRO RGB Indoor · RGB


Channel Compatibility

: No pixelation


Universal



Architectural




Main lighting




NOVA TAPE PRO RGB Indoor · RGB

Special lighting

BE6728




BE2009




: Slight pixelation

Universal


BE2601



BEI204



BEI205



Drivers

Non-dimmable

Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L*W*H)
KV-24030-ASW	30W	100-277VAC	24V	No	Yes	Dry/Damp	6.10" *2.12" *0.78"
KV-24060-ASW	60W	100-277VAC	24V	No	Yes	Dry/Damp	7.00" *2.40" *0.94"
KV-24096-ASW	96W	100-277VAC	24V	No	Yes	Dry/Damp/Wet	9.05" *2.75" *1.69"
KV-24150-ASW	150W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.07" *3.07" *1.85"
KV-24200-ASW	200W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.07" *3.07" *1.85"
KV-24300-ASW	300W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.86" *3.07" *1.85"

DMX512-dimmable

Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L*W*H)
KVX-24096-3C-A	96W	100-277VAC	24V	Yes	Yes	Dry/Damp/Wet	9.05" *3.07" *0.98"
KVX-24150-3C-A	150W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.90" *3.07" *0.98"
KVX-24200-3C-A	200W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.90" *3.07" *0.98"
KVX-24300-3C-A	300W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	11.85" *3.07" *0.98"

DMX Decoders


Code	Description
LT-903	3 channels output, up to 576W output power
LT-912	12 channels output, up to 1152W output power
LT-924	24 channels output, up to 1728W output power

Controllers


Code	Description
DINA-DR micro	DMX 60 channels, DMX Stand Alone controller with 10 scenes, USB connectivity for programming
SLESA-U9	DMX 256 channels, USB connection, standalone mode with 1 area and 20 scenes
STICK-GA2	DMX 512 channels, ready to use (pre-loaded with 8 scenes and 170 RGB fixtures)
STICK-CW4	DMX 1024 channels, up to 36 scenes stored and directly recalled via 6 touch sensitive buttons

Wiring Diagram

DMX Control System



DMX Driver System



NOVA TAPE PRO RGB Indoor · RGB

Connectors (Optional, purchase for extra)



- NCO-STCN-4P-10**
Strip to cable connector without wire, for 0.39" (10mm) tape, 4 pin
- NCO-STC-4P-10**
Strip to cable connector with 5.91" (15cm) wire, for 0.39" (10mm) tape, 4 pin
- NCO-STSJ-4P-10**
Strip to strip jumper connector with 5.91" (15cm) wire, for 0.39" (10mm) tape, 4 pin
- NCO-STMKB-4P-10**
Strip to cable with black male & female connector, for 0.39" (10mm) tape, 4 pin
- NCO-STMKW-4P-10**
Strip to cable with white male & female connector, for 0.39" (10mm) tape, 4 pin



- NI4CO-STS-4P-10**
Strip to strip connector, for 0.39" (10mm) tape, 4 pin

Additional Accessories (Optional, purchase for extra)



- MCW-4P-67**
Male connector with 0.98' (30cm) white cable, 4 pin, IP67, Wet, 20 AWG
- FCW-4P-67**
Female connector with 0.98' (30cm) white cable, 4 pin, IP67, Wet, 20 AWG
- VHB**
VHB 3M adhesive back tape, stronger stickiness